

DHI-XVR4104/08/16HE

4/8/16 Channel Penta-brid 720P Mini 1U Digital Video Recorder



- Embedded processor
- Support HDCVI/AHD/TVI/CVBS/IP video inputs
- Max 5/10/18 channels IP camera inputs
- Long transmission distance over coax cable
- Support 1 SATA HDD, up to 8TB



System Overview

Dahua, as a technology leader, is always the first ever developed the shining new technology in the security industry, and today we present XVR. As the perfect solution to upgrade existing video surveillance systems, XVR supports penta-brid access technology such as HDCVI, AHD, TVI, CVBS and IP to effortlessly integrate with popular industry formats, offering an affordable solution loaded with flexible options. It supports up to 4/8/16 channels of HDCVI/AHD/TVI/CVBS inputs, and 1/2/2 channels IP camera additionally, 16 channels local live-view channels, and 16 playback channels.

Designed as a full compatibility product, XVR is able to provide end user the simplicity of analog system, namely lower system cost, simple installation and use of existing cable. It is ideal for a wide range of applications such as public safety, retail store, transportation, home protection and education.

Functions

HDCVI/AHD/TVI/CVBS Auto-detect

The XVR can auto recognize the signal of front-camera without any setting. It makes operation more friendly and convenient.

5MP Resolution

The XVR supports up to 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing.

Smart Search

This function helps you get more motion detect video during a short time through drawing a region when playback. It is very useful when an emergency occurs.

P2P

Monitor at anytime and anywhere. Easily and conveniently manage the device.

Technical Specification

System

| | |
|------------------|--------------------|
| Main Processor | Embedded Processor |
| Operating System | Embedded LINUX |

Display

| | |
|----------------------|--|
| Interface | 1 HDMI ,1 VGA |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768 |
| Multi-screen Display | 4CH: 1/4/6 8CH: 1/4/8/9/16 16CH: 1/4/8/9/16/25 |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording |

Video Detection and Alarm

| | |
|-----------------|---|
| Trigger Events | Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips |
| Video Detection | Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Tampering |
| Alarm input | 8/8/16 |
| Relay Output | 3 |

Playback and Backup

| | |
|-------------------|---|
| Playback | 4CH: 1/4 8CH: 1/4/9 16CH: 1/4/9/16 |
| Search Mode | Time /Date, Alarm, MD and Exact Search (accurate to second) |
| Playback Function | Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom |
| Backup Mode | USB Device/Network |

Storage

| | |
|--------------|--------------------------------|
| Internal HDD | 1 SATA Port up to 8TB capacity |
| eSATA | N/A |

Auxiliary Interface

| | |
|-------|-------------------------|
| USB | 2 USB Ports (2 USB 2.0) |
| RS232 | N/A |
| RS485 | 1 Port, for PTZ Control |

Third-party Support

| | |
|---------------------|---|
| Third-party Support | Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more |
|---------------------|---|

Audio and Video

| | |
|--------------------|---|
| HDCVI Camera Input | 4/8/16 Channel |
| IP Camera Input | 4+1:each channel up to 2MP 8+2/16+2:each channel up to 5MP |
| Audio In/Out | 4/8/16 Channel Input, 1 Channel Output, RCA |
| Two-way Talk | Reuse audio in(channel 1)/out, RCA |

Recording

| | |
|-----------------|--|
| Compression | H.264 |
| Resolution | 1080N,720P, 960H, D1, HD1, BCIF, CIF, QCIF |
| Record Rate | Main Stream: 4CH:1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) 8/16CH:1080N(12fps)/720P(15fps)/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Sub stream:4CH:CIF/QCIF(1~15fps) 8/16CH:CIF/QCIF(1~7fps) |
| Bit Rate | 1Kbps ~ 6144Kbps Per Channel |
| Record Mode | Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop |
| Record Interval | 1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec |

Network

| | |
|------------------|---|
| Interface | 1 RJ-45 Port (100M) |
| Network Function | HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP, Alarm Server, P2P,IP Search (Support Dahua IP camera, DVR, NVS, etc.) |
| Max. User Access | 128 users |
| Smart Phone | iPhone, iPad, Android |
| Interoperability | ONVIF 2.42, CGI Conformant |

Electrical

| | |
|-------------------|--------------------|
| Power Supply | DC12V/2A |
| Power Consumption | <10W (Without HDD) |

Environmental

| | |
|----------------------|---|
| Operating Conditions | -10°C ~ +55°C (+14°F ~ +131°F), 0~ 90% RH |
| Storage Conditions | -20°C ~ +70°C (-4°F ~ +158°F) , 0~ 90% RH |

Construction

| | |
|--------------|--|
| Dimensions | Mini 1U, 325mm×255mm×55mm (12.8" x 10" x 2.2") |
| Net Weight | 1.5kg (3.3 lb) (without HDD) |
| Gross Weight | 2kg (4.4lb) |
| Installation | Desktop installation |


Certifications

| | |
|----------------|---|
| Certifications | FCC: Part 15 Subpart B ICES 003 Issue 6 |
| | CE:EN 55032:2012+AC:2013(Class B) EN 55024:2010 EN 61000-3-2:2014 EN 50130-4:2011 EN 61000-3-3:2013 |
| | UL 60950-1 and CAN/CSA C22.2 No.60950-1-07 |


| Ordering Information | | |
|----------------------|---------------|---|
| Type | Part Number | Description |
| 4/8/16 Channel XVR | DHI-XVR4104HE | 4 Channel Penta-brid 720P Mini 1U Digital Video Recorder |
| | DHI-XVR4108HE | 8 Channel Penta-brid 720P Mini 1U Digital Video Recorder |
| | DHI-XVR4116HE | 16 Channel Penta-brid 720P Mini 1U Digital Video Recorder |

Rear Panel


DHI-XVR4104HE



DHI-XVR4108HE



DHI-XVR4116HE



Dimensions (mm)

